





































Type	CRE15-08 AN-F-A-E-HQOE				
Model	A96814574P11551				
f	60	Hz	P2	11,0	kW
n	3529	min ⁻¹	H _{max}	163	m
Q	20.5	m ³ /h	H	130.1	m
p _{max} /t _{max}	16/120	bar/°C	CCW		
Serial No.	0002	Ass. in AU			
			CE EAC		
MEI ≥	0.7	η _p (%)	72,5	GRUNDFOS DK-8850 Bjerringbro, Denmark	

DE	7309BE	NDE	6309.Z.C4
Grease	UNIREX N3	Quantity	13 g
T _{amb}	40 °C	Interval	4500 h
T _{amb}	- °C	Interval	- h

96694508

GRUNDFOS® 

Type : MGE160MB2-FF300-F3	Serial No :12093	DE : 7309BE	IP : 55	TP211
P.N. : 85905508 - V02	P.C. : 1521	NDE: 6309.Z.C4	Tamb: 40 C	CL : F
Env.Type :3R	PF :0,90	Wgt : 118 kg	Var : C9-S ADVANCED I/O, GENI/RS485	
INPUT		OUTPUT		Eff: IE3 91,2%
U in : 3 ~ 380-480	V	U out: 0-Uin	V	     
I in 1/1 :	22,5-18,8	A	P2 : 11,0	
f in :	50/60	Hz	f out : 0-120	
		Hz	Hz	

31705815

CRE, CRIE, with pressure sensor

CRNE mit Drucksensor

GRUNDFOS



The logo is a light blue, teardrop-shaped graphic with a white double-line border. It is positioned on a dark, textured surface, with a circular hole visible above it.

Grundfos
blueflux®

GRUNDFOS

