



SPECIFICATION

HOPPER DRYERS

Model	Diameter mm(in)	Height mm(in)	Capacity kg(□ b)	Heater Power (kw)	Blower Power (w)	Weight kg(□ b)	Applicable Injectioner (OZ.)
THD-12ET	280(11.0)	790(31.1)	12(26.4)	2.1	90	27(59.4)	1
THD-25ET	350(13.8)	965(38.0)	25(55)	2.7	90	39(85.8)	3
THD-50ET	430(16.9)	1140(44.9)	50(110)	3.9	200	51.5(133.3)	5-8
THD-100ET	550(21.7)	1390(54.7)	100(220)	6	250	82(180.4)	10-30
THD-200ET	700(27.6)	1660(65.4)	200(440)	10	400	137(301.4)	30-60
THD-400ET	850(33.5)	2130(83.9)	400(880)	20	400	223(490.6)	60 up

THD-50EDS-MB Controller Body				THD-50-EDS-HP Hopper			Capacity kg (□ b)	Heating Power (kw)		Air Flow m ³ /min(F ³ /min)	
Width mm(in)	Height mm(in)	Depth mm(in)	Weight kg (□ b)	Diameter mm(in)	Height mm(in)	Weight kg (□ b)		Drying Heater	Regeneration Heater	Dryer	Regeneration
820 (32.2)	1640 (64.6)	550 (21.7)	280 (616)	520 (20.5)	1500 (59.1)	90 (198)	50 (110)	4.2	2.1	1.25(CMM) 45(CFM)	0.3(CMM) 10.8(CFM)