





















































RUN STOP FWD REV



PRG ▲ RUN  
ENTER ▼ STOP  
DISP

**⚠ WARNING**

1. Refer to the instruction manual before installation and operation.
2. Do not connect AC power to output terminals UVW
3. Do not remove any cover while applying power and at least 10 min. after disconnecting power
4. Securely ground (earth) the equipment



MODEL: SS2100-1.5KW-3PH-65

INPUT: 3PH 415V 50Hz/60Hz

OUTPUT: 3PH 415V 4.0A 120% 60S

FREQ RANGE: 0.1-400Hz 1.5kW



20061506275-2069



**SAMT** Australia



MADE IN ENGLAND

869

BS5000-99

A.C. MOTOR

 BARKER-SIDDELL

Brook Crompton Park  
CAMPBELLTOWN N.S.W.

Nr AE90L

E155912

kW 1.5

A 3.5

N 1420

V 415Δ

IP55

Hz 50

PHASE 3

CLASS II

IND. CAT. MC

80% RISE

SEC V

SEC A

DESIGN



SAA CERT. No	AUS.Ex230-1981
GROUP No	Exd 11B T4
TYPE No	AE90L
Exd No	EX74042
PEAK AMBIENT TEMP	40 °C

846





可搬攪採機  
大阪 東京

400658-400659-428747号

510 動力 750 Wolt

75470 製造 4.4

回転・60~1700・60~1700

空防機

化学機織工業株式会社